

# 2559-RTD

## 8-Channel RTD Input Module



100Ω, 120Ω, 130Ω, 200Ω, 500Ω, 1000Ω, 10Ω,  
9.03Ω

2,3, 4 wire  
250μA  
1000Ω per lead wire (max)

30VDC or VAC continuous

10Ω Cu: -100°C to 260°C (-148°F to 500°F)  
100Ω Pt: -200°C to 850°C (-328°F to 1562°F)  
120Ω Pt: -80°C to 260°C (-112°F to 500°F)

°C, °F, ohms (selectable)  
±0.1°C, ±0.2°F  
0.1°

100Ω Pt 0.9°C (1.6°F) from 0-60°C  
Ωx100 0.36Ω from 0-60°C

25 mSec (all channels, no filtering)

The 2559-RTD is a high-speed 8-channel RTD input module designed to be compatible with the SIMATIC® 505 I/O base. The Model 2559-RTD translates RTD input signals into scaled temperature values.

>130db @ 60Hz

>80db @ 60Hz  
1500 VDC channel-to-PLC

- CTI 2500 Series™ or Simatic® 505 base format
- 1500V channel-PLC backplane isolation
- Fast 25ms update time for all channels
- Detects open in RTD or field wiring
- Compensates for lead resistance

3 wire 100Ω platinum  
Digital filtering enabled  
Degrees C

standard CTI 2500-40F 40-position re-  
moveable connector, 14-22 AWG

2.8W @ 5 VDC  
Single-wide  
0° to 60°C (32° to 140°F)  
-40° to 85°C (-40° to 185°F)  
5% to 95% (non-condensing)  
UL, ULC, CE, FM

8 RTD input channels

(Class 1, Div.2)

1.5 lb. (0.68 Kg)

Platinum 0.003850 (European DIN)  
Platinum 0.003916 (American)  
Platinum 0.003902  
Platinum 0.003920  
Copper 0.004274  
Nickel 0.006720  
Nickel 0.006178 (European DIN)



Control Technology Inc.

5734 Middlebrook Pike, Knoxville, TN 37921-5962  
Phone: +1.865.584.0440 Fax: +1.865.584.5720  
www.controltechnology.com

